

Multi Position Meter Warm-Up Station Model 5101

- Smart Socket™
- WATT-Net™ Software
- Testboard Options



Multi Position Meter Warm-Up Station Model 5101

Introduction

The Model 5101 Meter Warm-Up System is a multi-position board designed to power meters. When you need to power a group of meters to program, the Model 5101 is the answer. Meter socket bypassing allows the testboard to run with less than a full complement of meters. Meter form numbers must be identical for each run. Testboard operation at end-of-test is also programmable.

The Model 5101 is a PC based system that provides an operator interface that is easy to learn and use, yet powerful and flexible. All setup information is clearly displayed on a high-resolution color monitor. The operator's job is greatly simplified by the use of single key commands, programmable default tables, and on-line user help screens.

Features

- Number of test stations: *Available in 6, 9, 12 and 15 station configurations*
- Test voltage: *60-540V*
- Potential clips closed for testing
- Minimal insertion force Smart Socket™
- PC Minimum System: *Dell™ standard business class Mini Tower PC • 17" flat screen monitor • Microsoft Windows®*
- Windows® compatible Upscale™ software
- WATT-Net™ data acquisition system



Options

- Single or multi stator A-base adapters — 2 per bay (top and bottom)
- Barcode reader and software

Specifications

- Source: *30A, 240V, 4 wire, 3Ø delta or 30A, 208V, 4 wire 3Ø Y (specify with order)*
- Meter forms tested: *1S-6S, 8S-17S, 19S, 21S, 25S, 26S, 29S, 35S, 36S, 45S, 46S, 56S, or 66S*
- Dimensions: *(19.5" per three test station bay + 1.5)" W × 71.25" H × 33" D cabinet model with writing ledge 30" above base
Twelve (12) stations 82.5" W*
- Housing: *All aluminum construction*
- Weight: *Twelve (12) stations — Approximately 1,300 lbs*
- Warranty: *Two (2) year limited warranty (all parts and labor)
Manufacturer's warranty on computer*

